


UPGRADE

ICONA Pro

LED street lighting fixture





UPGRADE

ICONA Pro XL

Absolute safety and aesthetic appeal.

This range is available in four different sizes, ensuring the same design and performance across a variety of installation settings.

TECHNICAL DESCRIPTION

LED lighting fixture for street lighting, **NITEKO** brand, **ICONA PRO** series, **XL** model, suitable for mounting on arm or post-top (adjustable from +15° to -15° in 5° steps) with a standard mounting compatible with **60 mm** poles, requiring no adaptors or reducers. Adapters for poles/arms with a diameter of **76 mm** are available on request.

Luminaire equipped with **high-power LEDs** powered by a constant current up to a maximum of **500mA**, with a correlated colour temperature of **3,000K** in the standard version, or with optional CCTs of **1,800K, 2,200K, 2,700K, 3,000K, 5,000K**, a colour rendering index (**CRI**) greater than **70** in the standard version, or **CRI>80** or **CRI>90** on request, and a photobiological risk class not exceeding **RG1**.

LEDs fitted with high-precision **PMMA secondary collimators** for focusing the light beam, with an overall minimum optical system efficiency of not less than **86%**, a wide choice of photometric curves suitable for any type of application, featuring asymmetrical, rotosymmetrical, elliptical light beams, or for pedestrian crossings, with a luminous intensity class of no less than **G*2**; all are **full cut-off**, in full compliance with legislation against light pollution, with zero luminous intensity beyond 90° in their standard installation position.

Light source

Light source efficiency greater than **190 lm/W** (3,000 K) and lifetime, under optimal operating conditions, of:

- Lifespan 100,000 h (L95 B10: $T_a = 25\text{ °C}$; $IF \leq 500\text{mA}$);
- Lifespan 120,000 h (L90 B10: $T_a = 25\text{ °C}$; $IF \leq 500\text{mA}$);
- Lifespan 270,000 h (L80 B10: $T_a = 25\text{ °C}$; $IF \leq 500\text{mA}$);
- Lifespan 450,000 h (L70 B10: $T_a = 25\text{ °C}$; $IF \leq 500\text{mA}$).

Fixture's luminous flux from **21,515lm** to **38,625lm**, with luminous efficacy greater than **135lm/W** (3,000K) depending on the configuration (number of LEDs and supply current, CCT, CRI, optics) and an energy efficiency rating higher than **A++**.

Power

Fixture with an effective power output of between **160.5 W** and **200.2 W** with 175–264V AC – 50/60Hz power supply in the standard version, or 120–277V AC – 50/60Hz power supply available on request in the optional version. High-efficiency electronic drivers integrated into the electrical compartment of the luminaire, characterised by a power factor greater than **PF>0.95** with a failure rate of less than 12% after 100,000 hours of operation and a minimum efficiency of **90%**.

In the standard version, the power supply unit comes with the following functions:

- Pre-programmed automatic dimming for up to 5 daily time profiles (PRG5);
- Control via a 1–10 V analogue signal (DIM);
- Constant lighting control during the lifetime (CLO.LITE).

Protection

Thermal protection, short-circuit protection and standard surge protection up to **10kV** in common mode and **6kV** in differential mode. On request, the luminaire can be equipped with an **SPD device** integrated into the electrical compartment, providing surge protection up to **10kV, 12kV** or **20 kV**, in both common mode and differential mode.

EOS-free luminaire equipped with specific technical features designed to prevent the formation of parasitic capacitance, thereby minimising damage caused by electrical overstress (EOS).

VOC-free luminaire constructed using non-metallic materials and components with high chemical compatibility with the LED source to prevent the release of volatile organic compounds (VOCs) that could affect performance, stability and colour temperature over time.

Class II insulated luminaire (or optional **Class I**) with an **IP66** rating for the optical and electrical compartments, impact resistance rating of **IK09**, with an operating temperature range of **-40°C** to **+50°C** and a storage temperature range of **-40°C** to **+80°C**, consisting of:

- die-cast aluminium body with a built-in heat sink dimensioned to ensure a long service life and maximum efficiency of the diodes; the body has undergone sandblasting, cataphoresis and polyester powder coating in the standard **white aluminium RAL 9006** (other colours available on request), VOC and EOS free, , resistant to corrosion, abrasion, flaking and salt spray, with testing up to 1,000 hours;
- optical and electrical compartments separated by a sealed partition;
- optical compartment accessible by removing the tempered glass screen and the relevant stainless steel sealing screws, and electrical compartment that can be opened tool-less, by clips;
- adjustable accessory for post-top or mast arm mounting, made of die-cast aluminum and secured to the luminaire body by means of screws. The screws properly secured allow installation in either of the two mounting configurations, with a possible inclination of **-15° / +15°** in **5°** steps;

- built-in spirit level (gradienter) to ensure perfectly horizontal installation;
- 5mm-thick extra-clear tempered glass screen with silicone rubber gasket shaped to the geometry of the optical compartment, which ensures the air-tightness of the fixture;
- LED modules assembled on the fixture's body using screws only, without the use of adhesives or special glues, to facilitate maintenance and replacement;
- high-efficiency modular PMMA optical components assembled on the LED modules using special fixing screws; these can be removed to allow for easy replacement during maintenance;
- available on request with an H07RN-F outgoing cable fitted with a pair of IP66/IP68 plug-and-socket connectors for quick and safe connection to the mains.


Remote-control

On request, the luminaire can be equipped with a **remote-control** interface integrated into the luminaire body, available in the following versions:

- Control via DALI and DALI2.0 digital signals (DALI/DALI2.0);
- Automatic flux dimming according to pre-programmed settings (CLO-FULL);
- Voltage variation regulation (PLV);
- Power line carrier regulation (LPL);
- Interface with emergency lighting devices (DCE-DIM);
- Radio-frequency control (Nema Socket and Zhaga Socket).

Certifications

This appliance complies with product standards and meets the Minimum Environmental Criteria (CAM) in accordance with Ministerial Decree of 27 September 2017 (Official Gazette No. 244 of 18 October 2017).



*Pending

TECHNICAL SPECIFICATIONS

MAIN

Features

Luminaire type	LED street lighting fixtures
Applications	Urban and extra-urban lighting, large areas, roundabouts, squares and car parks
Brand	Niteko
Series	ICONA PRO
Model	XL
Mounting	Post-top or mast arm with inclination of $-15^{\circ} \div +15^{\circ}$ in 5° steps; Standard accessory: compatible with $\varnothing 60\text{mm}$ poles/arms; Optional accessory: compatible with $\varnothing 76\text{mm}$ poles/arms;
Effective power	160.5 W – 200.2W (Tolerance +5%)
Luminaire efficacy	$\eta_{\text{app}} \geq 135 \text{ lm/W}$ (3,000K)
Operating temperature	Operating temperature: -40°C to $+50^{\circ}\text{C}$; Storage temperature: -40°C to $+80^{\circ}\text{C}$
Estimated service life	L95 B10: $> 100.000 \text{ h}$ ($T_a = 25^{\circ}\text{C}$; $\text{IF} \leq 500\text{mA}$); L90 B10: $> 120.000 \text{ h}$ ($T_a = 25^{\circ}\text{C}$; $\text{IF} \leq 500\text{mA}$); L80 B10: $> 270.000 \text{ h}$ ($T_a = 25^{\circ}\text{C}$; $\text{IF} \leq 500\text{mA}$); L70 B10: $> 450.000 \text{ h}$ ($T_a = 25^{\circ}\text{C}$; $\text{IF} \leq 500\text{mA}$);
Certifications	CE, RoHS, ENEC, ENEC+ (pending), IP66, IK09, 1,000h hour salt spray test, photobiological safety, photometric certification, EOS Free, VOC Free, Shock&Vibration Test.

OPTICAL

Features

Light source	High-power LEDs powered by a constant current of less than 500mA
Optical system	Independent and replaceable PMMA LED and optical modules
Source luminous flux	From 21,515lm (10W 1,800K CRI>70) TO 38,625lm (200W 4,00K CRI>70) (Tolerance $\pm 5\%$)
Source luminous efficacy	$\eta_{\text{LED}} \geq 190 \text{ lm/W}$ (3,000K)
Colour temperature	Standard: 3.000K; Optional: 1,800K, 2,200K, 2,700K, 4,000K, 5,000K, 5,700K
Colour Rendering Index	Standard: CRI>70; Optional: CRI>80, CRI>90
Photometry	Asymmetrical, rotosymmetrical, elliptical and for pedestrian crossings
Optical Efficiency	75-86%
Photometric classes	Luminous intensity class G*2; Glare index class D.6
Photobiological safety	Risk class: RG1; IR and UV radiation: absent
Switch-on/re-switch-on time	$t_A < 1\text{sec.}$; $t_R < 1\text{sec.}$

ELECTRICAL**Features**

Power supply	Standard: 175/264 V a.c. – 50/60 Hz; Optional: 120/277 V a.c. – 50/60 Hz; Electronic power supplies built into the appliance's electrical compartment with efficiency $\eta > 95\%$ and power factor $PF > 0.97$ (Active PFC). Available standard functions: - Pre-programmed automatic dimming for up to 5 daily time profiles (PRG5); - Control via a 1–10 V analogue signal (DIM); - Constant lighting control during the lifetime (CLO.LITE).
Electrical connection	Standard: safety isolating switch with disconnection upon opening of the electrical compartment Optional: outgoing power supply cable with an IP68 electrical connector
Insulation class	Standard: Class II; Optional: Class I
Electrical protection	Standard: surge protection up to 10kV in common mode and 6kV in differential mode Optional: additional protection with an SPD device built into the electrical compartment, protecting the unit up to 10kV, 12kV or 20 kV, both in CM and DM.

MECHANICAL**Features**


Materials	Body and brackets: die-cast aluminium with built-in heat sink; Adjustable mounting bracket: die-cast aluminium integrated into the body; Screen: 5 mm thick extra-clear flat tempered glass; Optics: PMMA modular optics; Gaskets: silicone; Screws: A2 stainless steel (external screws); zinc-plated carbon steel (internal screws).
Colour	Standard: RAL 9006; Optional: other RAL colours available on request
Protection rating	Optical compartment: IP66; Electrical compartment: IP66; Impact resistance: IK09
Dimensions and weight	690 x 333 x 94 mm; 8,4kg Mast arm mounting: 850 x 333 x 108 mm Post-top mounting: 705 x 333 x 238 mm

LIGHTING FEATURES


PRODUCT ITEM CODE	POWER	NOMINAL LUMINOUS FLUX (xxxyy)					
		4070	3070	2270	3080	2270	1870
		5070		3580		2780	2790
				4080			
				5080			
				5780			
	W	lm					
ICONAPRO-XL-180W-xxyy-zz-rr	160,5	30.506	28.864	28.216	26.310	25.521	21.515
	170,1	32.943	31.162	30.470	28.405	27.553	23.228
	180,3	34.681	32.810	32.078	29.907	29.010	24.457
ICONAPRO-XL-200W-xxyy-zz-rr	180,4	35.177	33.251	32.536	30.308	29.399	24.787
	200,2	38.625	36.517	35.725	33.287	32.288	27.222

TECHNICAL DRAWINGS

ICONA PRO XL

Mast arm
mounting

a 690 mm
a1 850 mm
b 333 mm
h 94 mm
h1 108 mm
Øp 60 mm (pole) x
115 mm (depth)

Post-top
mounting

a 690 mm
a2 705 mm
b 333 mm
h 94 mm
h2 238 mm
Øp 60 mm (pole) x
115 mm (depth)

Weight 8,4 kg


Wind exposure surface

Base 0,22 m²Side 0,05 m²


PHOTOMETRIC DATA




Asymmetrical




A1 - 150° x 50°
 η 83,8% - G*6




A2 - 140° x 45°
 η 84,7% - G*4




A3 - 90° x 60°
 η 86,7% - G*6




A4 - 145° x 55°
 η 82,9% - G*4




A7 - 140° x 70°
 η 79,1% - G*2



A8 - 155° x 60°
 η 81,9% - G*1




A9 - 145° x 55°
 η 85,2% - G*4




A10 - 155° x 65°
 η 75,6% - G*2




Black light stop




AB2 - 140° x 50°
 η 84,6% - G*3




AB4 - 145° x 60°
 η 83,9% - G*3




BA2 - 140° x 45°
 η 78,7% - G*4



BA3 - 90° x 60°
 η 81,1% - G*6



BA4 - 145° x 65°
 η 77,0% - G*3




BA9 - 145° x 75°
 η 81,3% - G*4


PHOTOMETRIC DATA



Elliptical




E3 - 145° x 110°
η 87,0% - G*6



E4 - 140° x 100°
η 81,4% - G*6




Rotosymmetrical




R1 - 140° x 140°
η 82,1% - G*6



Pedestrian crossings



PCDX - R65° x 60°
η 85,4% - G*6




PCDX - R65° x 60°
η 85,4% - G*6

ICONA PRO XL MODEL



MOUNTING EXAMPLES



REFERENCE





NITEKO s.r.l.

Viale della Libertà, 8
74020 Montemesola (TA) - Italia
Tel +39 099 567 12 19
Fax +39 099 567 11 12
e-mail info@niteko.com

niteko.com